

# OTP

<b>TERMINAL</b>	平形	<b>FLAT 110 TERMINAL</b>
-----------------	----	--------------------------

[mm]

品番	表面処理	ワイヤレンジ	材質	板厚	D	L	W	E	備考
Part No.	Finish	Wire range [mm <sup>2</sup> ]	Material	Thick- ness					Remarks


平形110TAB(多極)/ **110 FLAT TAB for multi-poles** 適合(Mating) REC 211012, 211412

*	211011	0, 2M	0.5~1.25	Brass	0.5		20.4	2.79	12.0	
	211031	0**, 2M**	0.2~0.35	Brass	0.5		20.4	2.79	12.0	

\* 211011-0Aもあります。

\*\* 注文品番/Ordering No. : 211031-0-A, 211031-2MA

110 FLAT TAB for multi poles




平形110REC(多極)/ **110 FLAT REC for multi-poles** 適合(Mating) TAB 211011, 211031

*	211012	0, 2M	0.5~1.25	Brass	0.25		15.4	3.7	6.12	
	211412	0**, 2M**	0.2~0.35	Brass	0.25		15.4	3.7	6.12	

\* 211012-0A, 211012-2MAもあります。

\*\* 注文品番/Ordering No. : 211412-0A, 211412-2MA

110 FLAT REC for multi poles




平形110TAB(単極)/ **110 FLAT TAB for single-pole** 適合(Mating) REC 211022, 211032

	211021	2	0.5~1.25	Brass	0.5		20.4	2.79	12.0	
	211041	2*	0.2~0.35	Brass	0.5		20.4	2.79	12.0	

\* 注文品番/Ordering No. : 211041-2A

110 FLAT TAB for single-pole





平形110REC(単極)/ **110 FLAT REC for single-pole** 適合(Mating) TAB 211021, 211041

	211022	0*, 2, 2M*	0.5~1.25	Brass	0.25		15.4	3.7	6.3	適合(Mating) TAB t 0.5
	211032	0, 2, 2M	0.2~0.35	Brass	0.25		15.4	3.7	6.3	適合(Mating) TAB t 0.5

(UL No. E98924 : 211022-2, 211032-2 AWG#22)

\* 注文品番/Ordering No. : 211022-0A, 211022-2MU


110 FLAT REC for single-pole



PL06形REC

PL06C6-010A	2M	0.2~0.5	Brass	0.25		16.0	3.7	8.0	適合(Mating) TAB t 0.5
-------------	----	---------	-------	------	--	------	-----	-----	-------------------------

PL06形REC



<b>TERMINAL</b>	平形	<b>FLAT 187,205 TERMINAL</b>
-----------------	----	------------------------------

[mm]



品番	表面処理	ワイヤレンジ	材質	板厚	D	L	W	E	適合タブ厚さ
Part No.	Finish	Wire range [mm <sup>2</sup> ]	Material	Thick- ness					Mating TAB thickness

平形187REC(単極)/ **187 FLAT REC for single-pole**



218732	1, 2	0.5~1.25	Brass	0.32		15.0	5.6	6.35	TAB t0.5
218752	2	AWG24~#20	Brass	0.32		15.0	5.6	6.35	TAB t0.5
218762	1, 2	0.5~1.25	Brass	0.32		15.0	5.6	6.35	TAB t0.8

(UL NO. E98924 : 218732-2, 218752-2, 218762-2)

187 FLAT REC for single-pole



187 FLAT FLAG REC for single pole





平形187旗型REC(単極)/ **187 FLAT FLAG REC for single-pole**

218734	1, 2	0.5~1.25	Brass	0.32		13.2	5.6	6.35	TAB t0.5
218738	2	0.5~1.25	Brass	0.32		13.2	5.6	6.35	TAB t0.5 低挿入

(UL NO. E98924 : 218734-2)

205 FLAT REC for single-pole



平形205REC(単極)/ **205 FLAT REC for single-pole**


220532	1, 2	0.75~2.0	Brass	0.4		15.65	6.35	6.35	TAB t0.8
220534	2	0.75~2.0	Brass	0.4		15.65	6.35	6.35	TAB t0.5
220552	2	0.3 ~0.75	Brass	0.4		15.65	6.35	6.35	TAB t0.8
220554	1, 2	0.3 ~0.75	Brass	0.4		15.65	6.35	6.35	TAB t0.5
220556	1, 2	0.3 ~0.75	Brass	0.4		15.65	6.35	6.35	TAB t0.52

(UL NO. E98924 : 220532-2, 220534-2, 220552-2, 220554-2)

<b>TERMINAL</b>	平形	<b>FLAT 250 TERMINAL</b>
-----------------	----	--------------------------


[mm]

250 FLAT TAB for multi poles




品番	表面処理	ワイヤレンジ	材質	板厚	D	L	W	E	備考
Part No.	Finish	Wire range [mm <sup>2</sup> ]	Material	Thick-ness					Remarks
平形250TAB(多極)/ <b>250 FLAT TAB for multi-poles</b>					適合(Mating) REC 225012, 225312, 225412				
225001	2M	0.5~2.0	Brass	0.4	—	24.4	6.08	13.85	T=0.83
225011	0, 2M	0.5~2.0	Brass	0.4	φ 2.0	24.4	6.08	13.85	T=0.83
225301	2M	2.0~3.0	Brass	0.4	—	24.4	6.08	13.85	T=0.83
225311	0, 2M	2.0~3.0	Brass	0.4	φ 2.0	24.4	6.08	13.85	T=0.83
225411	0	0.3~0.75	Brass	0.4	φ 2.0	24.4	6.08	13.85	T=0.83
225421	0	0.3~0.5	Brass	0.4	φ 2.0	24.4	6.08	13.85	T=0.83

250 FLAT REC for multi poles




平形250REC(多極)/ <b>250 FLAT REC for multi-poles</b>					適合(Mating) TAB 225001, 225011, 225311, 225411, 225301, 225412				
225012	0, 2M	0.5~2.0	Brass	0.32		19.4	7.5	7.75	
225312	0, 2M	3.0	Brass	0.32		19.4	7.5	7.75	
225412	0, 2M	0.3~0.5	Brass	0.32		19.4	7.5	7.75	

250 FLAT lance-less TAB for multi poles




平形250ランスレスTAB/ <b>250 FLAT lance-less TAB for multi-poles</b>					適合(Mating) REC 225402, 225502, 225902				
225401	0	0.3~0.5	Brass	0.4		24.4	6.0	14.0	T=0.8
225501	0	0.5~2.0	Brass	0.4		24.4	6.0	14.0	T=0.8

250 FLAT lance-less REC for multi poles




平形250ランスレスREC/ <b>250 FLAT lance-less REC for multi-poles</b>					適合(Mating) TAB 225401, 225501				
225402	0	0.3~0.5	Brass	0.32		19.4	7.5	7.75	
225502	0	0.5~2.0	Brass	0.32		19.4	7.5	7.75	
225902	0	3.0	Brass	0.32		19.4	7.5	7.75	

250 FLAT TAB for single-pole



平形250TAB(単極)/ <b>250 FLAT TAB for single-pole</b>					適合(Mating) REC 225022, 225322, 225422, 225032, 225432, 225342				
225021	0, 2	0.5~1.25	Brass	0.8	φ 2.0	19.7	6.35	8.0	
225121	2	0.5~1.25	Brass	0.8	φ 1.65	19.7	6.35	8.0	

250 FLAT REC for single-pole



平形250REC(単極)/ <b>250 FLAT REC for single-pole</b>					適合(Mating) TAB 225021				
225022	0, 1, 2	0.5~2.0	Brass	0.32		19.4	7.5	7.75	適合(Mating) TAB t0.8
225322	0, 2	3.0	Brass	0.32		19.4	7.5	7.75	適合(Mating) TAB t0.8
225422	0, 2M	0.3~0.5	Brass	0.32		19.4	7.5	7.75	適合(Mating) TAB t0.8

OTP


<b>TERMINAL</b>	平形	<b>FLAT 250 TERMINAL</b>
-----------------	----	--------------------------

[mm]

品番	表面処理	ワイヤレンジ	材質	板厚	D	L	W	E	備考
Part No.	Finish	Wire range [mm <sup>2</sup> ]	Material	Thick- ness					Remarks
平形250REC(単極)/ <b>250 FLAT REC with window for single-pole</b>					適合(Mating) TAB 225021				
225032	1.2	0.75~2.0	Brass	0.43		19.3	7.6	7.8	適合(Mating) TAB t0.8
225432	1.2	0.3 ~0.75	Brass	0.43		19.3	7.6	7.8	適合(Mating) TAB t0.8
225832	1.2	0.75~2.0	Brass	0.43		18.9	7.6	7.8	適合(Mating) TAB t0.8

(UL NO. E98924 : 225032-2, 225432-2, 225832-2)


250 FLAT REC with window for single-pole



平形250旗形REC(単極)/ <b>250 FLAT FLAG REC for single-pole</b>					適合(Mating) TAB 225021				
225342	1, 2	0.5~2.0	Brass	0.45		15.0	8.05	7.75	適合(Mating) TAB t0.8

(UL NO. E98924 : 225342-2)

250 FLAT FLAG REC for single-pole




OTP

<b>TERMINAL</b>	平形	<b>FLAT 350 TERMINAL</b>
-----------------	----	--------------------------


[mm]

品番	表面処理	ワイヤレンジ	材質	板厚	D	L	W	E	備考
Part No.	Finish	Wire range [mm <sup>2</sup> ]	Material	Thick- ness					Remarks
平形350TAB(多極) / <b>350 FLAT TAB for multi-poles</b>					適合(Mating) REC 235012, 235312, 235412, 235912				
235011	0, 2M	0.5~2.0	Brass	0.4		29.3	7.8	16.0	T=0.8
235311	0, 2M	3.0	Brass	0.4		29.3	7.8	16.0	T=0.8
235911	0, 2M	5.0	Brass	0.4		29.3	7.8	16.0	T=0.8

350 FLAT TAB for multi-poles





350 FLAT REC for multi-poles



平形350REC(多極) / <b>350 FLAT REC for multi-poles</b>					適合(Mating) TAB 235011, 235311, 235911				
235012	0, 2M	0.5~2.0	Brass	0.4		24.35	9.0	12.1	
235014	2M	0.5~2.0	Equivalent to PB	0.4		24.35	9.0	12.1	
235312	0, 2M	3.0	Brass	0.4		24.35	9.0	12.1	
235412	0	0.3	Brass	0.4		24.35	9.0	12.1	
235912	0	5.0	Brass	0.4		24.35	9.0	12.1	

350 FLAT REC for single-pole



平形350REC(単極) / <b>350 FLAT REC for single-pole</b>									
235052	0, 2M	0.5~2.0	Brass	0.4		24.35	9.0	12.1	適合(Mating) TAB t0.8
235054	2M	0.5~2.0	Equivalent to PB	0.4		24.35	9.0	12.1	適合(Mating) TAB t0.8
235452	0	0.3	Brass	0.4		24.35	9.0	12.1	適合(Mating) TAB t0.8