


(DIP 3.2mm Standard)



(DIP 2.4mm)

■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000MΩ min
- Temperature Range : 1.PBT -40°C ~ +85°C
2.Nylon 6T -25°C ~ +105°C
- Contact Resistance : 20mΩ max

■ BOX HEADER

- Part No. : JS-1200-XX X (XX)

Poles No.

Blank : DIP 3.2mm

D : DIP 2.4mm

Blank: PBT UL94V-0

6TNH: Nylon 6T UL94V-0, Halogen Free

- Poles : 6-64(DIP, Straight)
- Material : Contact : Brass, Gold Plated
Base : Refer the above narrative
- Q' ty : 1000 pcs./PVC Box

Poles	Dimensions (mm)		
	A	B	C
6	5.08	15.24	12.94
8	7.62	17.78	15.48
10	10.16	20.32	18.02
12	12.70	22.86	20.56
14	15.24	25.40	23.10
16	17.78	27.94	25.64
20	22.86	33.02	30.72
24	27.94	38.10	35.80
26	30.48	40.64	38.34
30	35.56	45.72	43.42
34	40.64	50.80	48.50
40	48.26	58.42	56.12
44	53.34	63.50	61.20
50	60.96	71.12	68.82
60	73.66	83.82	81.52
64	78.74	88.90	86.60

PART NO	JS-1200-XX
2.54mm Box Headers DIP Type(Straight)	

SCALE	UNIT	TOLERANCE	
	mm	.0	±0.30
		.00	±0.20
PROJ	VER NO.	.000	±0.10
	a7	ANGLE	
DATE	SIZE	0°	±1°
	A4	.0°	±
	SHEET	1/1	

LTR	REVISION RECORD	NAME	DATE
CUSTOMER			
Conforms to The RoHS Instruction			